

Republic of the Philippines PAMANTASAN NG LUNGSOD NG MAYNILA

(University of the City of Manila) Intramuros, Manila

PLM - BIDS and AWARDS COMMITTEE (PLM-BAC)

REQUEST FOR QUOTATION (RFQ)

The Pamantasan ng Lungsod ng Maynila, through its Bids and Awards Committee (BAC), invites suppliers/manufacturers/distributors/contractors to quote for the hereunder project:

Project: Purchase of Office Equipment and IT Equipment and Software for CY 2013 of

Various Offices [Negotiated Procurement after Two (2) Failed Biddings]

ABC: PhP1,085,500.00

Item	End-		Unit of	Item Description		Unit	Total Cost
No.	user(s)	Qty.	Issue			Cost	(ABC)
2	Emeritus	1	Unit	Brand New and Brande	d Laptop Computer	30,000.00	270,000.00
	CM	5		ISO Certification	Manufactured by an ISO 9001 or ISO 9002 certified Manufacturer		
	CAE	1			At least 2 cores 4 threads or equivalent		
	GSE	1		Processor	 At least 2.2 GHz processor 		
	GSM	1			 At least 3 MB L3 Cache 		
	total	9		Memory On-Board	At least 2Gb DDR3 1333		
				Hard Disk	SATA Hard Disk At least 500Gb capacity		
				CD-ROM Drive	At least SATA Internal DVD-ROM Drive At least 8X DVD		
				Display Screen	At most 14" HD; 1366 x 768 pixel resolution At least 10/100 Mbps built-in		
				Network	network interface Built-in wireless LAN, and Built-in bluetooth		
				Bundled Software (Pre-installed; updated for security fixes and definition files as of time of delivery; tested for production compatibility and configured for optimal use.) Battery Life Accessories Weight Documentation Warranty Certificate Post Warranty	Operating Systems (Dual Boot) (1) Licensed proprietary commercial OS (latest user-friendly OS and popularly-used by non-IT users) 32/64 bit, as appropriate (2) Latest version of a free open- source OS With utility/diagnostic software, back-up software and recovery CD, if applicable. Productivity Suites Latest version of a free open-source office suite At least 4.0 hours (6 cells li-ion) Built-in webcam and Carrying bag At most 2.4 kg User's Guide and Technical Manuals At least 1 year on all parts and services At least 3 years post warranty		
				Burn Test Quality	support on availability of parts At least 3 continuous days		
				Assurance	(Certification to be issued by the Distributor/Supplier)		
3	CM	7	Unit	Branded and Brand nev	v LED Monitor	5,000.00	35,000.00
				ISO Certification	Manufactured by an ISO 9001 or ISO 9002 certified Manufacturer		

				I			
				LED Panel			
				Туре	47cm / 19" LED		
				Display Area	At least 19" or 18.5" effective size		
				True Resolution	1366 x 768		
				Contrast Ratio	1000:1 (Typ), 10000000:1 (DCR)		
				Brightness	250 cdm/m ² (typ)		
				Viewing Angle	170° (H), 160° (V) (CR≥10)		
				Response Time	5ms		
				Panel Surface	Anti-Glare, Hard Coating (3H)		
				Light Source	30,000hrs		
				Input Signal			
				Analog	RGB Analog (75 ohms, 0.7 /1.0 Vp-p)		
				Frequency	Fh: 24~82khz; Fv: 50~75		
				Sync	Separate Sync		
				Compatibility			
				PC	VGA up to 1366 x 768 Non		
				Mac	Interlaced 1366 x 768		
				Connector	1500 A 700		
					1 v15 nin mini D cub		
				Analog Power	1 x15 pin mini D-sub		
					AC 100 220V (Universal)		
				Voltage	AC 100-220V (Universal); 50/60Hz(Switch)		
				Consumption Controls	18W (typical) / 22W (maximum)		
				Basic	[1], [2], Power, Down, Up		
				OSD (On Screen Display)	Auto Image		
				(OIT SCIECTI DISPINY)	Adjust Contrast/Brightness, Audio		
					Adjust		
					Volume, Mute Color Adjust, sRGB,		
					9300K, 7500K, 6500K, 5000K, User		
					Color [R, G, B] Information, Manual Image Adjust, H/V Position, Horizontal		
					Size, Fine Tune, Sharpness, Dynamic Contrast, Aspect ratio, Eco		
					mode, Setup Menu Language Select,		
					Resolution		
					Notice, OSD Position, OSD timeout, OSD		
					Background, Auto Power Off,		
					Memory Recall		
				Weight			
				Net	3.4 Kgs.		
				Regulations	CB,WEEE, RoHS, REACH SVHC List, EuP, TCO5.0, Windows XP / Vista		
					Basic,		
					ERGO, GOST-R+Hygienic, UkrSEPRO, BSMI, PSB, C-TICK, KC,		
					SASO, Energy Star 5.0; Certified for		
					Windows 7		
6	TREAS	1	Unit	Branded & Brand New (Color Laser Printer (Mid-Range)	30,000.00	90,000.00
	GSM	1		ISO Certification	Manufactured by an ISO 9001 or ISO 9002 certified Manufacturer		
	CMC	1		D	At least 20ppm (Black and white,		
				Print speed	and Color)		
	total	3		First-page out time	Not more than 20 seconds		
				Resolution	At least up to 600x600 dpi		
				Memory	At least 128MB installed memory		
				Interface	At least USB 2.0 port		
				Paper handling	With at least 50 sheet capacity multi-		
					purpose tray With at least 250 sheet standard		
					With at least 250 sheet standard capacity tray		
	l		1		capacity traj	l	

	1	1					
				Media Types	Must accept, at least, the following		
					media types:		
					 Plain paper 		
					 Transparencies 		
					Envelopes		
					• Labels		
				Media Sizes	Must accept the following media		
					sizes: 1) Standard Tray, cut sheet		
					a) A4, Letter		
					b) Legal, 8.5 x 13		
					c) Executive, A5		
					Multi-purpose Tray, cut sheet		
					a) Custom: at least 3 x 5 to 8.5 x		
					14 in.		
					Drivers for Windows XP, Windows 8,		
				Printer Drivers	Window 7 32/ 64 bit, Mac OS X and		
				Print Processor	Linux At least 540Mhz		
				Fillit Flocessoi	USB cable, power cable, drivers and		
				Accessories	manuals		
				Warranty	At least 1 year on parts and service		
				,	At least 3 years post-warranty		
				Support	support on availability of parts		
8	PSO	1	Unit	Branded & Brand New	All-in-One Colored Printer	10,000.00	10,000.00
				ISO Certification	Manufactured by an ISO 9001 or ISO 9002 certified Manufacturer		
				Functions	Print, Copy, Scan, Fax		
				Black print Speed	Up to 28ppm		
				Color print Speed	Up to 22ppm		
				Resolution	At least up to 600x600 dpi black, at least up to 1200x1200 dpi color		
				Memory	At least 16MB installed memory		
				Control Panel	With print job cancellation button and status indicator		
				Paper handling	With at least 100 sheets input tray, 20-sheet automatic document feeder		
				Media Types	Must accept, at least, the following media types:		
					Plain paper		
					Transparencies		
					 Envelopes 		
				Media Sizes	Must accept the following media		
					sizes: Standard Tray, cut sheet		
					a. A4, Letter		
					b. Executive, A5		
					c. Custom: at least 77 x 127 to 216		
					x 356 mm		
				6 6	Flatbed, ADF		
				Scanner Specifications	Scan resolution : At least up to 1200 dpi		
				6 1 6 16 1	Copy speed: Up to 28 cpm		
				Copier Specifications	Resolution: At least 600x1200 dpi black, at least 1200x1200 dpi color		
				Fax	Resolution: up to 300 x300 dpi Speed and memory: 3 sec/ page;		
					up to 100 pages		
				Print Processor	Speed dials: up to 90 numbers At least 192Mhz		
					At least USB 2.0 port		
				Connectivity Printer Drivers	Drivers for Windows XP, Windows 8, Window 7 32/ 64 bit, Mac OS X and		
					Linux USB cable, power cable, drivers and		
				Accessories	manuals		
				Warranty	At least 1 year on parts and service		
				Support	At least 3 years post-warranty		
	1	1	Ì	1	support on availability of parts	Ī	1

12	СМ	1	Unit	Branded & Brand New	Multifunction Copier (High-End)	95,000.00	95,000.00
				Functions	Print, Copy, Scan		
				Model or Type	Desktop		
				Technology	Laser		
				Copy/Print speed	At least 20ppm		
				Scan speed	At least 20ipm		
				First-Copy Output time	Not more than 7.2 seconds		
				Resolution	At least up to 600x600 dpi		
				Memory	At least 256MB and maximum- 512MB		
				Interface Connectivity	At least USB 2.0 port, Ethernet (100Base-TX / 10Base-T)		
				Paper Handling	With at least 250 sheet paper capacity – Paper Cassette		
					With at least 100 sheet paper capacity- Stack Bypass		
					With at least 50 sheet paper capacity- Automatic Feeder		
				Media Sizes	Maximum A3 size		
				Power Consumption	Approximately 150kw max		
				Weight	Approximately 50 kg.		
				Printer Drivers	Drivers for Windows 7 (32/64 bit), Windows Vista (32/64-bit), and Windows XP Pro (32/64-bit), Server 2003/2008/Mac OSX (10.4.4 or later)		
				Warranty	At least 1 year on parts and service		
				Support	At least 3 years post-warranty		
					support on availability of parts		
15	CPT	1	Unit	Branded and Brand Ne		25,000.00	75,000.00
	GSL	1		ISO Certification	Manufactured by an ISO 9001 or ISO 9002 certified Manufacturer		
	CMC	1		Display technology	DLP		
	total	3		Brightness (ANSI Lumens)	At least 2,700 ANSI Lumens		
				Resolution	Native SVGA (800x600)		
					At least UXGA (1,600 x 1,200)		
					1080p (1,920x 1,080)		
				Video Compatibility	NTSC, PAL, SECAM, HDTV, EDTV, and SDTV		
				Aspect Ratio	At least 4:3 and supported 6:9		
				Contrast Ratio	At least 7,500:1		
				Zoom adjustment	Manual or Automatic		
				Focus adjustment	Manual or Automatic		
				Projection Screen Size (d	liagonal)		
				Minimum	Not less than 24" (61cm)		
				Maximum	At least 300" (762cm)		
				Projection Distance	3.3" (1.0m) – 37.2" (11.3m)		
				Throw Ratio	53" @ 2m (1.86-2.04:1)		
					55 @ ZIII (1.00-2.0 7 .1)		
				Keystone correction	Manual or Automatic		
				Adjustment	Manual or Automatic		
				Vertical	At least ± 40°		
				Lamp life			
				Normal	At least 5000 hours		
				Economy	At least 6000 hours		
				Lamp warranty	At least 90 days or 500 hours		
				Input terminals			
				RGB	At least 1 mini D-SUB 15 pin		
				Video	At least 1 RCA		
				S-Video	1 DIN 4 pin		
				Weight	Not more than 3 kgs.		
				Product warranty	At least 1 year on parts and service		
1				Post-warranty support	At least 5 years post-warranty		
					support on availability of parts		

				Accessories included	Remote control, VGA cable, carrying		
	0014				case, and power cord	25 222 22	
16	GSM	7	Unit	Branded and Brand Ne	_	25,000.00	350,000.00
	GSHS	2		ISO Certification	Manufactured by an ISO 9001 or ISO 9002 certified Manufacturer		
	CLA	1		Display technology	LCD		
	CET	3		Brightness (ANSI Lumens)	At least 2,500 ANSI Lumens		
	GSASE	1		Resolution	At least XGA (1024 x 768)		
	total	14		Weight	Not more than 3 kgs.		
				Contrast Ratio	At least 3000:1		
				Zoom adjustment	Manual or Automatic		
				Focus adjustment	Manual or Automatic		
				Image size (diagonal)			
				Minimum	Not less than 20 inches		
				Maximum	At least 250 inches		
				Throw distance			
				Minimum	1.5 meters or shorter		
				Maximum	7.0 meters or longer		
				Keystone correction			
				Adjustment	Manual or Automatic		
				Vertical	At least ± 30°		
				Lamp life			
				Normal	At least 4000 hours		
				Economy	At least 5000 hours		
				Lamp warranty	At least 90 days or 500 hours		
				Input terminals			
				RGB	At least 1 mini D-SUB 15 pin		
				Video	At least 1 RCA		
				S-Video	1 DIN 4 pin		
				Product warranty	At least 1 year on parts and service		
				Post-warranty support	At least 5 years post-warranty support on availability of parts		
				Accessories included	Remote control, VGA cable, carrying		
	LIDO				case, and power cord	11 000 00	44.000.00
17	URC	1	Unit	Branded & Brand New		11,000.00	11,000.00
				Scanner type Scan Speed	Flatbed At least 7 seconds		
				Resolution	At least 4800dpi x 9600dpi		
				Scanner button	Copy, Scan, Scan to PDF, email		
				Document size	A4, letter		
				Interface	USB 2.0		
				LAMP	LED		
				Document type	Transparencies, Plain paper, Film		
				Software driver	for Windows XP, Windows Vista, Windows 7, Windows 8, Linux, Apple		
				File scan format	BMP, JPEG, GIF, TIFF, PNG, PDF, Plain text, rich text		
				Certification	Energy Star Certified		
				Accessories	USB cable, Power adaptor , CD drivers and Manual		
					1 year on Parts and Services, and at		
				Warranty	least 5 years post warranty support on availability of parts		
18	GSASE	1	Unit	Branded & Brand New		10,000.00	10,000.00
				Туре	Portable Document Camera		
				Pixel Count	3.2 mega pixels		
				Lamp Type	LED Light		
				White Balance Exposure	Auto / Manual Auto / Manual		
				Image Mode	Text / Graphics / High Frame		
				Effect	Color / B/W / Negative		
				Focusing	Manual		
		_					

	1		1	T		ı	
				Shooting Area	At least 330mm x 248mm (maximum)		
				Zooming	Up to 8X digital zoom		
				Power Source	DC 12v, 100-240V, 50-60Hz		
				Consumption	At least 18 watts (lamp- off); 20 watts (lamp-on)		
				Input/ Output	RGB input- 15-pins D-sub (VGA), RGB output- 15-pins D-sub (VGA)		
					S-Video, Composite Video, USB, Power Jack		
				Weight	At least 3.0 kg		
				Warranty	At least 1 years on all parts, labor		
19	CMC	1	Unit	Photo Editing Software	and services	20,000.00	20,000.00
	Cite	_	Offic	Filoto Luiting Software	Creative Design Application (Latest	20,000.00	20,000.00
				Category	user-friendly and popularly-used version in the market) Professional photo editing, graphic		
				Product Description	design, web design / publishing, and digital imaging software Drawing, painting, measuring and		
				Minimum Tools	navigation, selection, typing and retouching		
				Language Supported	Universal English		
				Platform Supported	PC		
				Operating System Supported	Microsoft XP SP3 or later, Microsoft Windows 7 SP1 or later		
				Distribution Media	DVD-ROM		
				License Type	Academic License		
				Documentation	User's Guide and Manuals		
				Warranty	At least 1 year on support and		
20	OEVP	4	Unit	*	services. Jninterruptible Power Supply	3,800.00	34,200.00
			Offic	(500VA)	Julia Cappi,	3,000.00	3 1/200100
	TREAS	1		ISO Certification	Manufactured by an ISO 9001 or ISO 9002 certified Manufacturer		
	HRDO	3		Capacity	300 Watts/ 500 VA		
	ICO	1		Form Factor	Mini tower		
	total	9		Number of IEC 320 outlets	At least 4		
				Runtime	At least 7 minutes at 50% load, at least 2 minutes at full load		
				Input voltage tolerances	180V-266V		
				Output voltage on	230 V		
				battery power Battery type	Maintenance-free sealed lead-acid		
				Bundled Software	Driver for MS Windows		
					Cord management straps, User		
				Accessories	manual		
				Warranty	At least 2 year on parts and service		
				Post Warranty	At least 4 years post warranty support on availability of parts		
				A ! . L !!!L .	Model readily available in the local		
				Availability	market.		
					Model meets the minimum technical specifications without modification or customization.		
21	PSO	2	Unit		Jninterruptible Power Supply	6,200.00	24,800.00
	Acctg.	2		(650VA) ISO Certification	Manufactured by an ISO 9001 or ISO 9002 certified Manufacturer		
	total	4		Capacity	400 Watts / 650 VA		
				Form Factor	Mini tower		
				Number of IEC 320 outlets	At least 4		
				Runtime	At least 7 minutes at 50% load, at least 2 minutes at full load		
				Input voltage tolerances	180V-266VAC, single phase		
				Output voltage on battery power	230 V		
				Battery type	Maintenance- free sealed lead-acid		
		i	i			Ī	

				Bundled Software	Driver for MS Windows		
					Cord management straps, User		
				Accessories	manual		
				Warranty	At least 2 year on parts and service		
				Post Warranty	At least 4 years post warranty support on availability of parts		
				A . 11 . L 112	Model readily available in the local		
				Availability	market.		
					Model meets the minimum technical specifications without modification or		
					customization.		
22	BPO	2	Unit	Branded & Brand New	External Storage ISO 9001:2008	6,000.00	48,000.00
	ITC	2		ISO Certification	Manufactured by an ISO 9001 or ISO		
	СМ	1			9002 certified manufacturer; At least 10 years of satisfactory		
					trade presence/existence		
	HRDO	1		Serial Transfer Rate	USB 3.0		
	OVPFP	1			Serial Bus Transfer Rate (USB 3.0) 5Gb/s (Max)		
	COA	1			USB 2.0		
	total	8			Serial Bus Transfer Rate (USB 2.0)		
				Dhil Caracifications	480Mb/s (Max)		
				Physical Specifications	Capacity 2TB		
					Interface USB 3.0 (Backward compatible with USB 2.0)		
				Physical Dimension	4.3" x 3.2" x 0.70"		
					Height 0.70 inches =		
					18mm Depth 4.3 inches =		
					110mm		
					Width 3.2 inches =		
					83.0mm Weight 0.45 pounds =		
					0.20kg.		
				Power Supply	USB powered directly from USB port of the PC, no separate power supply		
				,	needed		
				Temperature	Operating 41°F to 95°F		
24	ITC	1	11:4	Daniel de de Daniel Marie	Non operating -4°F to 149°F	2 500 00	2 500 00
24	ITC	1	Unit	9001:2008	External Drive (DVD-RW) ISO	3,500.00	3,500.00
				ISO Certification	Manufactured by an ISO 9001 or ISO		
				155 55.45445	9002 certified manufacturer;		
					At least 10 years of satisfactory trade presence/existence		
				Drive Type	DVD Writer		
				Enclosure Type	External		
				Drive Height	Slim (9.5mm)		
				Loading Type	Tray		
				Interface	USB 2.0		
				Drive Mounting	Horizontal / Vertical		
				Buffer Memory	1.5mb		
					DVD-RAM, DVD+R, DVD+R dual layer, DVD+RW, DVD-R, DVD-R dual		
				Supported Disc Format	layer, DVD-RW, DVD-R, DVD-R ddai		
				Supported Disc Format	video, CD-R, CD-RW, CD-ROM, CD-		
					ROM/XA, CD-audio, Video-CD, Photo-CD, CD-I (FMV), CD-Text		
				Data Transfer Rate	DVD+R		
					• Write: 8X (10.8mb/sec)		
					• Read: 8X (10.8mb/sec)		
	•				DVD-R		
					• Write: 8X (10.8mb/sec)		
					• Write: 8X (10.8mb/sec)		
					 Write: 8X (10.8mb/sec) DVD+R Dual Layer 		
					• Write: 8X (10.8mb/sec)		

					DVD D D . L .		
					DVD-R Dual Layer		
					 Write: 6X (8.1mb/sec) 		
					 Write: 8X (10.8mb/sec) 		
26	OUR	1	Unit	Branded & Brand New (Heavy Duty)	Automatic Voltage Regulator	4,000.00	4,000.00
				Style	Standalone		
				Power Output	600VA		
				Phase	Single Phase		
				Input Voltage	150-250V		
				Output Voltage	220V, 110V		
				Frequency	50Hz/ 60Hz		
				Insulation Resistance	More than 5 ohms at DC 500V		
				Power Factor	Better than 90% (input voltage 180V, output voltage 220V and at rated load		
				Warranty	At least 1 years on all parts, labor and services		
27	ITC	1	Unit	Toner Tracer		5,000.00	5,000.00
				Features	High Sensitivity		
					Ergonomic shape, balance weight		
					Volume control		
					Recessed "on" switch		
					Tip replacement without opening case		
					Battery-low indicator		
					Lanyard attachment point		
				Accessories	Free Battery; Users Manual; Carrying case		
					TOTAL AMOUNT, PhP		1,085,500.00

Note: The Distributor/reseller must indicate its tender in the order of presentation as above. Likewise, it must attach an official brochure of the item being offered for reference purposes during the TWG evaluation.

Prospective suppliers should quote their lowest price on the item/s listed below and state the shortest time of delivery and submit their quotation duly signed by their representative not later than seven (7) calendar days.

Post-qualification of the lowest calculated bid shall be conducted.

Request for Quotation (RFQ) documents will be available at the PLM-BAC Secretariat Office (Tel. No. 528-4592) to prospective suppliers.

PLM reserves the right to accept or reject any Bid, to annul the bidding process, and to reject all Bids at any time prior to contract award, without thereby incurring any liability to the affected Supplier or Suppliers.

The Pamantasan ng Lungsod ng Maynila assumes no responsibility whatsoever to compensate or indemnify suppliers for any expenses incurred in the preparation of the bid.

Approved by:

CARLOS M. CARLOS Chairman